



Manhole Covers Ireland

We cover everything!

Lowpark, Charlestown, Co. Mayo, Ireland.

Phone 094 9033 022 Fax 094 925 4970

Email: info@mhcireland.com web Site www.mhcireland.com

B125 / C250 PP Channel and Brickslot



End Cap



Sump Unit



500mm or 250mm Long
Brickslot Rodding Access Unit



Product Code	Length	Height	Width	Loading	Certification	Grating TYPE
MH-DC-BSC55	1000mm	55mm + 60mm	100mm	C250	CE	PP
MH-DC-BSC105	1000mm	105mm + 60mm	100mm	C250	CE	PP

FEAT URES:

Material Grade/s: Polypropylene

Basic Dimensions (mm): Length = 1000

External Width = 120

External Height = 135 / 185

Internal Width = 100

Internal Height = 55 / 105

Upstand Height = 60

Slot Size = 10 x 47.5

Waterway Area (slot unit inlets): 94cm²

Weight: 3kgs

Load Rating Classification: B125 (12.5 tonnes) when installed in block paved areas

C250 (25 tonnes) when installed in concrete

Features: - CE marked for compliance to BS EN1433:2002

- All-plastic non-rusting design

- Lightweight

- Up to 25 tonne rating (depending on installation)

- Available with matching end-cap

The **CE** marking identifies the certification assessment procedure and is marked on all the channels distributed on the market in compliance with the safety requirements.