



# Manhole Covers Ireland

**We cover everything!**

Lowpark, Charlestown, Co. Mayo, Ireland.

Phone 094 9033 022 Fax 094 925 4970

Email: [info@mhcireland.com](mailto:info@mhcireland.com) web Site [www.mhcireland.com](http://www.mhcireland.com)

## **POLYMOR Concrete A15 & B125 Drainage Channel**

### **POLYMOR CONCRETE DRAINAGE CHANNELS FOR D.I.Y. MARKET**



Polymor Concrete Channel CW Galvanised Grating  
1000mm Long



Also available with B125 Ductile Iron Grating



Polymor Concrete  
End Cap Outlet



Polymor Concrete  
End Cap

Product Code	Length	Height Overall	Width Overall	Loading	Certification	Grating TYPE
MH-DC-CS10.10A15	1000mm	90mm	120mm	A15	CE	Galvanised
MH-DC-CS10.10B125	1000mm	110mm	120mm	B125	CE	Ductile
MH-DC-A-CS10-SS	1000mm	90mm	120mm	A15	CE	Stainless Steel

#### **FEAT URES:**

Light type linear drainage are intended for **backyard areas**. Light type Polymor Concrete linear drainage system is intended for **class A15** pedestrian traffic areas and **class B125** passenger car traffic. The channels require additional concrete apron. Class A15 linear drainage is fitted with slit type steel grating. The grating is press fit. Light type class B125 linear drainage are fitted with slit cast iron gratings. The grating is locking bar fit.

The **CE** marking identifies the certification assessment procedure and is marked on all the channels distributed on the market in compliance with the safety requirements.

Trade name	SYTEC CS
Channel material	Polymer concrete
Edge profile type	None
Grating type	Galvanized steel, Ductile iron
Grating mounting method	Press fit / Locking bar
Height	5.0 cm to 11 cm
Width	10 cm
Slope option	None
Strength class	A15, B125
Conforms to	PN-EN 1433:2005 / A1-2007