



Manhole Covers Ireland

We cover everything!

Lowpark, Charlestown, Co. Mayo, Ireland.

Phone 094 9033 022 Fax 094 925 4970

Email: info@mhcireland.com web Site www.mhcireland.com

Clermont C250 Dished 385 x 315 LOCKED G & F

Clermont C250 Dished 4 Sided 385 x 315 LOCKED G & F



Group 3

For gullies installed in kerbside channels of the pavement which , extends to 0.5 m in the road and to 0.2 m top on the pavement, when measured from the edge.

Product Code	Clear Opening	Overall Size	Frame Height	Loading	Certification	Waterway Area
MH-GF-C-3931-LKD	390 x 315mm	545 x 470mm	100mm	C250	Kite Mark	745cm ²

Manhole Covers Ireland Code: **MH-GF-C-3931-LKD**

Manufactures Name, Kitemark and Product Code: **Binayak Hi-Tech Engineering Ltd, KM 584238 and GGH-C385315**

Sub-Category: C250 Hinged Dished Gully Grates & Frames

Material Grade/s: Spheroid Graphite Iron Grade EN-GJS-500-7 to BS EN 1563:1997.

Temporary Bitumen-based paint coating to BS 3416.

Basic Dimensions: Clear Opening = 385mm x 315mm

Overall size = 590mm x 520mm

Depth = 100mm

Weight: 29kgs

Waterway Area: 746cm²

Load Rating Classification: C250 (25 tonnes)

Features: - BSI Kitemark Certified to BS EN124:1994

(copy certificate available upon request)

- Captive hinge design to deter thieves
- Dished grating design to enable use with matching concrete drainage channels
- Supplied complete with M16 locking Bolt for added security

Intended Use: Group 3 – minimum Class C250.

For manhole covers and gullies for drain wells, installed in water run off areas along the side of pavements. The distance measured from the edge of the pavement extends by 0,5 m in the carriageway and for a maximum of 0,2 m on the pavement (see norm EN124 group 3).