



Manhole Covers Ireland


We cover everything!

Portland, Lorrha, Nenagh, Co. Tipperary E45 DH99.

Phone 094 9033 022 Fax 094 925 4970

Email: info@mhcireland.com Website: www.mhcireland.com

Cologne 365 x 310 D400 Locked Grating and Frame



Group 4

Inspection manhole cover in Spheroidal cast iron with load bearing capacity over 400 kN (40 tons), conforming to the load class D400 as set out by norm EN 124:2 2015

Product Code	Overall Size	Clear Opening	Frame Height	Waterway Area	3rd Party Certified
MH-GF-D-3631-LKD	519 x 395mm	365 x 310mm	100mm	780cm ²	Yes

Manhole Covers Ireland Code: **MH-GF-D-3631-LKD**

Manufactures Name: **MERT DOKUM.**

Sub-Category: D400 Hinged Gully Grates & Frames for use in carriageway kerbside areas and commercial/industrial areas. Complies Fully with UK Highways Authority HA 104/09 Standard

Material Grade/s: Spheroid Graphite Iron Grade EN-GJS-500-7. Bitumen-based paint coating to BS 3416.

Basic Dimensions: MH-GF-D-3631-LKD

Clear Opening = 365mm x 310mm

Overall size = 519mm x 395mm **Depth** = 100mm

Waterway Area: = 780cm²

Load Rating Classification: D400 (40 tonnes)

Features: - 3rd Party Certified to BS EN124-2 2015

(copy certificate available upon request)

- Captive hinge design to deter thieves

- 3-Sided Flange for installation against kerbs

Intended Use: Group 4 – minimum Class D400. For use in areas where cars and lorries have access, including carriageways, hard shoulders and pedestrian areas. (See norm EN 124 group 4). THE CHOICE OF THE CORRESPONDENT PRODUCT IS PART OF THE RESPONSIBILITY OF THE PROJECT ENGINEER. The National Roads Authority Design Manual for Roads and Bridges also recommends the use of class E600 for large traffic volumes (in excess of 1,500 vehicles) per day on national roads. IF IN DOUBT, WE SUGGEST CHOOSING THE SUPERIOR CLASS OF PRODUCTS.